

E-Z Arm®



Options

65 Watt Halogen Light Kit:
Improves worker visibility and productivity.

Damper:
Shut off air flow when not in use.

Blowers:
Several sizes available.

Silencer:
Reduces air flow noise for quieter operation.

Wall Brackets:
Maximizes installation versatility.

Adjustable Height Floor Stand:
Maximum height of 120 inches adds installation versatility.

Filtration Units:
HEPA, cartridge, and odor-control filter systems available based on application.

Boom Extensions:
System includes steel boom arm, boom arm wall bracket, tube kit, flex hose, and one transition to 8-in. dia.

Airflow Systems, Inc.® has a policy of continuous improvement, and reserves the right to change designs and specifications without notice.

Features & Benefits

Patented friction release pawl-and-sprocket design:
Engages positively when positioned, yet offers no resistance when removed.

7-, 10-, or 14-foot lengths:
Provides for high-volume collection with maximum reach.

Strong HDPE flat base joint:
Easy to install; HDPE bearing material works to seal base without collars or fittings.

Large 13-in. dia. inlet hood with 360° flange handle:
Easier hood positioning than single-handle designs.

Durable rounded duct constructed of 21-ga. aluminum:
Withstands industrial use, yet lightweight for easy operation. Powder coated inside and outside.

Hi-Flow spiral wire-reinforced hose.
Provides superior strength and resistance to sparks and embers.

Specifications

Construction:
21 ga. aluminum tube with spiral wire-reinforced Hi-Flow hose

Arm Lengths:
7 ft. (E-Z Arm® 7A07) , 10 ft. (E-Z Arm® 7A10), 14 ft. (E-Z Arm® 7A14)

Blower Pkgs (HP):
.75, 1.5, 3.0, 5.0, 7.5

Nominal Air Flow (CFM):
600 to 1500

Weight (lbs.):
E-Z Arm® 7A07 - 36 lbs., E-Z Arm® 7A10 - 40 lbs.,
E-Z Arm® 7A14 - 45 lbs.