

E-Z Arm® 2.5



Options

Filtration Units:

HEPA, cartridge, and odor-control filter systems available based on application.

Blower Packages:

Multiple options available to meet application-specific criteria.

Airflow Systems, Inc.® has a policy of continuous improvement, and reserves the right to change designs and specifications without notice.

Features & Benefits

2.5-in. dia. arm in 4- or 6-foot lengths
Provides for high-efficiency source-point collection for close work areas.

4.75-in. dia. flanged intake hood:
Increases collection area and efficiency.

Strong, extruded aluminum tubing:
Epoxy powder coated for corrosion resistance; lightweight for one-hand positioning.

Triple-joint section design:
Provides complete 360° range of movement, allows for positive positioning in any setup.

Heavy-duty stamped aluminum joints:
External friction adjustments can handle continued repositioning with losing position integrity.

Universal wall/table mounting bracket:
Allows multiple mounting options to maximize operator productivity and space usage.

Flange-up or flange-down design:
Allows table or wall mounting configuration.

Specifications

Construction:

18 ga. extruded aluminum seamless tube with spiral flex duct

Arm Lengths:

4 ft. (E-Z Arm® 2.5 2EO4) , 6 ft. (E-Z Arm® 2.5 2EO6)

Blower Pkgs (HP):

consult factory

Nominal Air Flow (CFM):

75 to 300

Weight (lbs.):

E-Z Arm® 2.5 2EO4 - 5 lbs., 2EO6 - 6 lbs.