



AL-6



Dimensions

Width: 66.00"
Height: 33.00"
Depth: 48.00"
Table Size: 66.25" W x 42.00" D

Options

- Silencer:**
 Reduces noise up to 3 dBA.
- Custom Cartridge Media:**
 For specific applications.
- After-Filters:**
 99.97% HEPA
- Center Divider and Side Shields:**
 Improves collection efficiency; reduces contaminant migration.
- Portability:**
 Integral caster allows unit to be easily moved.
- Regain Air:**
 Provides additional downdraft velocity in the work area.

Airflow Systems, Inc.® has a policy of continuous improvement, and reserves the right to change designs and specifications without notice.

Features & Benefits

Proprietary Cabinet Design:
 Helps meet NFPA 651 for processing and finishing aluminum when properly used and maintained.

Integral Collection Area and Work Surface:
 Draws contaminants away from workers' breathing zone without hindering movement; large work area meets range of applications.

Direct-Drive Blower:
 Higher static pressure, longer filter life and greater reliability; no belts or pulleys to replace.

Non-electrostatic Operation:
 High reliability, low maintenance.

Ultra-Seal® Filter Mounting:
 Eliminates contaminant bypass of filters.

Specifications

Construction:
 10/12/14 ga. welded steel, powder coated cabinet

Blower Pkg:
 Backward Incline
 Non-Sparking

Noise Level (dBA):
 77

Electrical:
 3.0 HP - 208/230/460/3/60, 9.2/8.0/4
 amps, Class II, Group E
 575/3/60 available

Downdraft Velocity (FPM):
 155

Weight (lbs.):
 850

05-08

05-08 AL-6 DOWNDRAFT TABLE