

F70R



Dimensions

Width: 26.00"
Height: 25.50"
Length: 66.00"

Options

Pressure Gauge Kit:
Indicates when filters require cleaning.

Silencer:
Reduces air flow noise for quieter operation.

Charcoal Adsorber Modules:
Refillable modules control gases and odors.

HEPA After-Filter:
provides 99.97% DOP efficiency.

Backwards Inclined Blower:
For operating at higher pressures.

Inlet Plenum

Floor Stand:
Allows on-floor mounting when on-machine or hanging mounts are impractical.

Airflow Systems, Inc.® has a policy of continuous improvement, and reserves the right to change designs and specifications without notice.

Features & Benefits

Capacities to 2500 CFM:
Handles toughest industrial applications.

Direct-drive Blower:
Long filter life and greater reliability; no belts or pulleys to replace.

Non-electrostatic Operation:
High reliability, low maintenance.

Ultra-Seal® Filter Mounting:
Eliminates contaminant bypass of filters.

High Efficiency Filter Media:
provides maximum effectiveness; low air-to-cloth ratio extends cycles between filter changes; filter changes easily without tools.

Prewired:
2 speed switch and cord. (std. motor)
ON-OFF toggle switch (opt. motors)

Specifications

Construction:
18 ga. steel cabinet, powder coated

Blower Pkg (HP):
.75 (2-speed)

Noise Level (dBA):
68/62 silencer

Electrical:
.75 HP, 115/1/60, 11.4 amps, 2-speed, std.
.75 HP, 460/1/60, 2.0 amps, opt.
.75 HP, 208-230/1/60, 3.9 amps, opt.
.75 HP, 220/1/50, 3.8 amps, opt.

Nominal Air Flow (CFM):
1400-2500, 60 Hz
1000-2000, 50 Hz

Weight (lbs.):
170