



E-Z Arm® II



Options

35 Watt Halogen Light Kit:
Improves worker visibility and productivity.

Damper:
Shut off air flow when not in use.

Silencer:
Reduces air flow noise for quieter operation.

Blowers:
Several sizes available.

Wall Brackets:
Maximizes installation versatility.

Adjustable Height Floor Stand:
Maximum height of 120 inches adds installation versatility.

Filtration Units:
HEPA, cartridge, and odor-control filter systems available based on application.

Boom Extensions:
System includes aluminum boom arm, boom arm wall bracket, tube kit, and flex hose.

Airflow Systems, Inc.® has a policy of continuous improvement, and reserves the right to change designs and specifications without notice.

Features & Benefits

4-in. dia. arm in 5- or 8-foot lengths:
Provides for high-efficiency collection and maneuverability in tight spaces.

Strong HDPE flat base joint:
Easy to install; HDPE bearing material works to seal base without collars or fittings.

Large 8-in. dia. inlet hood with 360° flange handle:
Easier hood positioning than single-handle designs.

Durable rounded duct constructed of 21-ga. aluminum:
Withstands industrial use, yet lightweight for easy operation.

Hi-Flow spiral wire-reinforced hose.
Provides superior strength and resistance to sparks and embers.

Specifications

Construction:
21 ga. aluminum tube with spiral wire-reinforced Hi-Flow hose

Blower Pkgs (HP):
0.75, 1.5, 3.0, 5.0, 7.5

Nominal Air Flow (CFM):
200 to 600

Weight (lbs.):
E-Z Arm® II 4E05 - 9 lbs.
E-Z Arm® II 4E08 - 11 lbs.