



02-013 ROLL-FLEX ECO

Specifications:

Blower package:

- 1phase/1 HP/115V/60Hz

Construction:

- 12/14/16 ga. welded steel, powder coated cabinet

Nominal CFM:

- 1400 CFM "Free-Blowing"

Extraction arm options:

- Ø6.5" diameter 10' long Flexi-I arm
- Ø6.5" diameter 10' long Flexi-I arm
- Without extractor arm

Filtration:

- With up to 99,9% filter efficiency the Mobi-Flex Cartridge Filters will clean the premises of welding fumes and light grinding dust. The cleaned air is re-circulated into the premises, with no heat loss at all. The access to the "maintenance-free" replaceable cartridge filter is easy and changing it takes just a couple of minutes.

Features & Benefits:

Complete, self-contained unit:

- Economical: immediately functional.

Direct-Drive Blower:

- Higher static pressure. longer filter life and greater reliability: non-sparking: no belts or pulleys to replace.

Non-electrostatic operation:

- High reliability, low maintenance.

Ultra-Seal filter mounting:

- Eliminates contaminant bypass of filters.

Jet pulse Filter Cleaning System:

- Highly efficient filter cleaning

Low foot-print cabinet:

- Easy placement access speeds filter change out and maintenance.

Available with included extraction arm:

- Extremely maneuverable internally supported Ø6.5" diameter 6.5' or 10' long flexi arm can be included

Casters included

- Great mobility

Easy Start / Stop

- On / off switch included

30 years experience of construction and production are at your disposal!
LEV-CO extraction systems are a combination of well tested solutions and new ideas.
LEV-CO is always a step ahead, but not expensive!