



03-065

03-065 WF-ECO

### Specifications:

#### Blower packages:

- 1phase/1.5 HP/115V/60Hz
- 3phases/1.5 HP/208-230/460V/60Hz
- 3phases/1.5 HP/575V/60Hz

#### Construction:

- 12/14/16 ga. welded steel, powder coated cabinet

#### Nominal CFM:

- 600 CFM @ 8" ESP

#### Extraction arm:

- Ø6.5" diameter 10' long Flexi-I arm

#### Filtration:

- With up to 99.9% filter efficiency the Wall-Flex Cartridge Filters will clean the premises of welding fumes and light grinding dust. The cleaned air is re-circulated into the premises, with no heat loss at all. The access to the "maintenance-free" replaceable cartridge filter is easy and changing it takes just a couple of minutes.

### Features & Benefits:

#### Complete, self-contained unit:

- Economical: immediately functional.

#### Direct-Drive Blower:

- Higher static pressure. longer filter life and greater reliability: non-sparking: no belts or pulleys to replace.

#### Non-electrostatic operation:

- High reliability, low maintenance.

#### Ultra-Seal filter mounting:

- Eliminates contaminant bypass of filters.

#### Jet pulse Filter Cleaning System:

- Highly efficient filter cleaning

#### Low profile cabinet:

- Easy access speeds filter change out and maintenance.

#### Extraction arm options available:

- Extremely maneuverable internally supported Ø6.5" diameter 5' to 17' long, or Ø8" diameter 6.7' to 17' long flexi arm is available

#### Easy Start / Stop

- On / off switch included

**30 years experience of construction and production are at your disposal!**  
**LEV-CO extraction systems are a combination of well tested solutions and new ideas.**  
**LEV-CO is always a step ahead, but not expensive!**

