

# F70R



## Dimensions

**Width:** 26.00"  
**Height:** 25.50"  
**Length:** 66.00"

## Options

### Pressure Gauge Kit:

Indicates when filters require cleaning.

### Silencer:

Reduces air flow noise for quieter operation.

### Charcoal Adsorber Modules:

Refillable modules control gases and odors.

### HEPA After-Filter:

provides 99.97% DOP efficiency.

### Backwards Inclined Blower:

For operating at higher pressures.

### Inlet Plenum

### Floor Stand:

Allows on-floor mounting when on-machine or hanging mounts are impractical.

*Airflow Systems, Inc.® has a policy of continuous improvement, and reserves the right to change designs and specifications without notice.*

## Features & Benefits

### Capacities to 2500 CFM:

Handles toughest industrial applications.

### Direct-drive Blower:

Long filter life and greater reliability; no belts or pulleys to replace.

### Non-electrostatic Operation:

High reliability, low maintenance.

### Ultra-Seal® Filter Mounting:

Eliminates contaminant bypass of filters.

### High Efficiency Filter Media:

provides maximum effectiveness; low air-to-cloth ratio extends cycles between filter changes; filter changes easily without tools.

### Prewired:

2 speed switch and cord. (std. motor)  
ON-OFF toggle switch (opt. motors)

## Specifications

### Construction:

18 ga. steel cabinet, powder coated

### Blower Pkg (HP):

.75 (2-speed)

### Noise Level (dBA):

68/62 silencer

### Electrical:

.75 HP, 115/1/60, 11.4 amps, 2-speed, std.

.75 HP, 460/1/60, 2.0 amps, opt.

.75 HP, 208-230/1/60, 3.9 amps, opt.

.75 HP, 220/1/50, 3.8 amps, opt.

### Nominal Air Flow (CFM):

1400-2500, 60 Hz

1000-2000, 50 Hz

### Weight (lbs.):

170