





F120 Free-Hanging Dust Collector

Features & Benefits

- **Capacities to 3800 CFM:**
Handles toughest industrial applications.
- **Non-electrostatic operation:**
High reliability, low maintenance.
- **Ultra-Seal® filter mounting:**
Eliminates contaminant bypass of filters.
- **High efficiency filter media:**
provides maximum effectiveness; low air-to-cloth ratio extends cycles between filter changes; filter changes easily without tools.
- **Prewired to junction box:**
For fast, easy installation.

Dimensions

Width:	25.00"
Height:	26.00"
Depth:	72.00"

Options

- **Class II Direct-Drive BI Blower:**
Higher static pressure, longer filter life and greater reliability; non-sparking; no belts or pulleys to replace.
- **Pressure Gauge Kit:**
Indicates when filters require cleaning.
- **Silencer:**
Reduces air flow noise for quieter operation.
- **Charcoal Adsorber Modules:**
Refillable modules control gases and odors.
- **HEPA After-Filter:**
provides 99.97% DOP efficiency.
- **Inlet Plenum**

Specifications

Construction:
16 ga. steel cabinet, powder coated

Blower Pkg (HP):
2.0

Noise Level (dBA):
75/69/silencer
79/75 Class II

Electrical:
2.0 HP - 208-230/460/3/60, 6.5/6.2/3.1 amps.
3.0 HP - 208-230/460/3/60, 9.2/8.0/4.0 amps.
2.0 HP - 190/380/3/50

Nominal CFM (in.):
2000-3800

Weight (lbs.):
330

10-02

10-02 F120