

SPECIFICATION:

FILTER 1 – HYDROTRON MODEL HWF-4-40-7.5

AUTOMATIC FILL SYSTEM

- ½” NPT CUT OFF VALVE TO ISOLATED UNIT FOR SERVICE
- ½” NPT ELECTRICAL SOLENOID ONLY ALLOWS MAKE UP WATER TO ENTER UNIT WHEN BLOWER IS ON
- AUTOMATIC ELECTRONIC FLOAT VALVE CONTROLS LEVEL OF WATER .
- MANUAL FILL OVERRIDE SWITCH FOR INITIAL FILLING OF WATER
- PRESSURE REGULATOR FOR INLET WATER SUPPLY WHEN UNIT IS RUNNING

BLOWER

- DIRECT DRIVE BACKWARD INCLINED AIR FOIL TYPE WITH CONED INLET FOR MAXIMUM EFFICIENCY
- NO BEARINGS TO GREASE OR BELTS TO CHANGE.
- FOUR POINT VIBRATION ISOLATORS
- HOUSED IN SOUND INSULATED CHAMBER
- ADJUSTABLE OUTLET LOUVER ALLOWS CONTROL OF SUCTION
- 7.5 HP TEFC MOTOR 208 / 230 / 460 VOLT
- BLOWERS RATED 4,000 CFM AT 6” / 8” TSP (TOTAL STATIC PRESSURE)

CABINET

- WELDED 12 GA. GALVANIZED STEEL WITH TWO PART COLD TAR EPOXY COATING ON ALL INTERIOR WET SURFACES
- INDUSTRIAL ACRYLIC ENAMEL (GULF BLUE) COATING ON EXTERIOR
- REMOVABLE CLEAR ACCESS PANEL FOR VIEWING AND ACCESS TO WET SECTION OF COLLECTOR
- INTERIOR BAFFLE SYSTEM ENSURES THROUGH MIXING OF WATER AND PARTICULATE
- CHEVRON STYLE MIST ELIMINATOR PACK COALESSES AND DRAINS DROPPLETS BACK INTO COLLECTOR
- DRAIN – 1 ½” DIA. MALE NPT WITH CAP
- OVERFLOW ½” NPT
- 12” DIA. INLET WITH 2” LIP

MOTOR STARTER

- MAGNETIC MOTOR STARTER WITH PUSH BUTTON ON / OFF BUTTON, OVERLOAD PROTECTION IN NEMA 1 BOX, 460 VOLT STANDARD
- FACTORY INSTALLED CONTROL VOLTAGE TRANSFORMER
- EVERYTHING PREWIRED AND READY TO HOOK UP TO YOUR DISCONNECT SWITCH

REQUIREMENTS

- 208 / 230 / 460 VOLT 3 PHASE POWER FOR BLOWER
- 25.3 / 22 / 11 AMPS
- MAKE UP WATER SUPPLY

SHIPPING WEIGHT

- APPROX. –1,300 LBS.

OVER ALL DIMENSIONS

- 40” WIDE x 48 “ DEEP x 95 “ HIGH

SPECIFICATION:

FILTER 1 – HYDROTRON MODEL HWF-4-40-7.5

OPTIONS

OPTIONS

CABINET CONSTRUCTION

- STAINLESS STEEL CONSTRUCTION
- EXPLOSION PROOF MOTORS
- SPARK RESISTANT BLOWER CONSTRUCTION
- CUSTOM PAINT COLOR
- SLUDGE CONVEYORS
- SLUDGE REMOVAL USING OUR VACUTRON PNEUMATIC OPERATED SYSTEM TO TRANSFER THE SLUDGE TO A 55 GALLON DRUM

ELECTRICAL

- ELECTRICAL ENCLOSURES - NEMA 12/13

ODOR CONTROL

- ACTIVATED CARBON, PURAFILL OR OTHER ADSORPTION MATERIAL , AVAILABLE IN REFILLABLE MODULES, REMOVES PROCESS ODORS AND GASSES NOT REMOVED BY THE WET COLLECTOR

SAFETY FILTERS

- ASHRAE OR HEPA AFTER FILTERS SOMETIMES REQUIRED WHEN RECYCLING AIR FROM EXTREMELY HAZARDOUS DUST APPLICATIONS. CAN INCLUDE VISIBLE OR AUDIBLE INDICATOR

WATER FILL CONTROL

- LOW WATER CUT OFF SWITCH, DISABLES COLLECTOR
- OVER FLOW WATER CUT OFF SWITCH